

Compare All: All **Car Amplifiers**



Hide similar features

[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)
[Add To Cart](#) [Remove](#)

Price \$99.99 \$119.99 \$149.99 \$149.99 \$159.99 \$159.99 \$169.99 \$199.99 \$199.99 \$209.99

Condition New Stock New Stock New Stock New Stock New Stock New Stock New Stock New Stock New Stock New Stock

Customer Reviews

Performance Rockford Fosgate Prime R125-2 Rockford Fosgate Prime R250-1 Rockford Fosgate Prime R250-1D Rockford Fosgate Punch P200-2 Rockford Fosgate Prime R250-4 Rockford Fosgate Punch P300-1 Rockford Fosgate Punch P300-2 Rockford Fosgate Prime R300-4 Rockford Fosgate Prime R500-1 Rockford Fosgate Punch P400-1

RMS Power Output (Wt x Channels) 40 x 2 150 x 1 125 x 1 50 x 2 40 x 4 150 x 1 75 x 2 50 x 4 320 x 1 200 x 1

Peak Power Output (Wt x Channels) --- N/A --- 415 x 2 --- 1275 x 1 --- N/A N/A 1535 x 1

Power at 2 Ohms (Wt x Channels) 65 x 2 250 x 1 250 x 1 100 x 2 65 x 4 300 x 1 150 x 2 75 x 4 500 x 1 400 x 1

Bridged Power (Wt x Channels) 125 x 1 N/A --- 200 x 1 125 x 2 N/A 300 x 1 150 x 2 N/A N/A

Minimum Impedance Bridged 4 N/A --- 4 4 N/A 4 4 N/A N/A

Minimum Impedance Unbridged 2 2 2 2 2 2 2 2 2 2

Best Frequency Response 20-20k Hz 20-130Hz Hz 20-250 Hz 20-20k Hz 20-20k Hz 20-20k Hz 20-20k Hz 20-20k Hz 20-130Hz Hz 20-20K Hz

THD at Rated RMS Power 1% 1% 1% 0.05% 1% 1% 1% 1% 1% 1%

Signal to Noise Ratio 70 dB 80 dB 75 dB 85 dB 70 dB 80 dB 85 dB 70 dB 85 dB 80 dB

Input Voltage 14.4v 14v 14.4v 14.4v 14.4v 14.4v 14.4v 14.4v 14v 14.4v

Features Rockford Fosgate Prime R125-2 Rockford Fosgate Prime R250-1 Rockford Fosgate Prime R250-1D Rockford Fosgate Punch P200-2 Rockford Fosgate Prime R250-4 Rockford Fosgate Punch P300-1 Rockford Fosgate Punch P300-2 Rockford Fosgate Prime R300-4 Rockford Fosgate Prime R500-1 Rockford Fosgate Punch P400-1

Amplifier Class AB AB D AB AB AB AB AB AB AB

Low-Pass Crossover 50-250 Hz 40-130 Hz 50-250 Hz 50-500 Hz 50-250 Hz 50-500 Hz 50-500 Hz 50-250Hz 40-130Hz 50-500 Hz

Frequency

Low-Pass Slope (dB/octave)	12 dB/oct	12dB/oct Butterworth	12 dB/oct	12dB/oct	12 dB/oct	12 dB	12dB/oct	12dB/octave Butterworth	12dB/oct Butterworth	12 dB/oct
High-Pass Crossover Frequency	80 Hz	N/A	N/A	50-500 Hz	80 Hz	50-500 Hz	50-500 Hz	80Hz	N/A	50-500 H
High-Pass Slope (dB/octave)	12 dB/oct	N/A	N/A	12dB/oct	12 dB/oct	12 dB	12dB/oct	12dB/octave Butterworth	N/A	12 dB/oct
Bass Boost	0-12 dB	0-12dB	0-12 dB	0-18dB	0dB, +6dB, +12 dB	0-18 dB	0-18dB	0, 6, 12dB	0-12dB	0-18 dB
Bass Boost Frequency	45 Hz	45 Hz	45 Hz	45 Hz	45 Hz	45 Hz	45 Hz	45 Hz	45 Hz	45 Hz
Fan Cooled	No	No	No	No	No	No	No	No	No	No
Fuse Rating	25	30	25	40	40	60	50	50	60	60
Speaker Level Inputs	No	No	No	No	No	No	No	No	No	No
Preamp Outputs	1 pair	1 pair	1 pair	No	No	No	No	No	1 pair	No
Width (inches)	7-3/4	7-11/16	7-11/16	8-7/8	12-1/8	8-15/16	9	7-3/4	17-1/4	9
Height (inches)	2-7/16	2-7/16	2-7/16	2-1/4	2-1/2	2-1/4	2-5/16	2-1/2	2-1/2	2-3/16
Depth (inches)	7-11/16	12-1/8	7-11/16	7-9/16	7-11/16	8-1/2	8-3/4	17-13/16	7-11/16	8-1/2
Parts Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
Labor Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1Year
	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual
	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research

[Hide similar features](#)

With us, you get the whole package. The perfect gift. Shipped free. Supported forever. **Details**