










Compare All: Component Subwoofers

	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate	Rockford Fosgate
									
	Add To Cart	Add To Cart	Add To Cart	Add To Cart	Add To Cart	Add To Cart	Add To Cart	Add To Cart	Add To Cart
	Remove	Remove	Remove	Remove	Remove	Remove	Remove	Remove	Remove
Price	\$59.99	\$69.99	\$69.99	\$79.99	\$79.99	\$89.99	\$89.99	\$99.99	\$99.99
Condition	New Stock	New Stock	New Stock	New Stock	New Stock	New Stock	New Stock	New Stock	New Stock
Customer Reviews									
Size	10 -inch	10 -inch	10 -inch	12 -inch	12 -inch	10 -inch	10 -inch	8 -inch	8 -inch
Impedance	4 ohms	2 ohms	4 ohms	4 ohms	4 ohms	2 ohms	4 ohms	8 ohms	4 ohms
Cone Material	Polypropylene	Mica injected poly	Mica injected poly	Mica injected poly	Mica injected poly	Mica injected Poly	Mica injected Poly	Kevlar reinforced paper	Kevlar reinforced paper
Surround Material	<u>Butyl rubber</u>	Poly-foam	Poly-foam	Poly-foam	Poly-foam	Poly-Foam	Poly-Foam	NBR	NBR
Ideal Sealed Box Volume (cubic feet)	0.75	0.59	0.59	1.02	1.02	0.7	0.7	0.23	0.23
Ideal Ported Box Volume (cubic feet)	N/A	1.4	1.4	1.79	1.79	1.4	1.4	0.65	0.65
Port diameter (inches)	N/A	4	4	4	4	4	4	2	2
Port length (inches)	N/A	13	13	9.3	9.3	13.7	13.7	6	6
Free-Air	No	No	No	No	No	No	No	No	No
Dual Voice Coil	No	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Sensitivity	86 dB at 1 watt	87 dB at 1 watt	87 dB at 1 watt	89 dB at 1 watt	89 dB at 1 watt	83 dB at 1 watt	83 dB at 1 watt	83.5 dB at 1 watt	83.5 dB at 1 watt
Frequency Response	24 - 250 Hz	45 - 250 Hz	45 - 250 Hz	43 - 250 Hz	43 - 250 Hz	38 - 250 Hz	38 - 250 Hz	41 - 250 Hz	39 - 250 Hz
RMS Power Range (Watts)	50-150	50-250	50-250	50-250	50-250	100-200	100-200	50-200	50-200
Peak Power Handling (Watts)	300	500	500	500	500	400	400	400	400
Top Mount Depth	4 7/16	4 7/16	4 7/16	5 1/4	5 1/4	3 7/16	3 7/16	4 3/8	4 3/8

(inches)

Bottom Mount Depth (inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Cutout Diameter or Length (inches)	9 1/8	9 1/16	9 1/16	11 1/8	11 1/8	9 1/16	9 1/16	7 1/16	7 1/16
Vas (liters)	85	39	39	66.4	68.8	20.4	21.7	12	12
Fs (Hz)	23.9	35	35	35	35	38.1	38.1	40.9	39
Qts	0.38	0.47	0.53	0.6	0.6	0.68	0.73	0.49	0.47
Xmax (millimeters)	5.8	6.5	6.5	6.5	6	8	8	5.3	5.3
Parts Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
Labor Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual
	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research	Hands-on Research

[Hide similar features](#)

With us, you get the whole package. The perfect gift. Shipped free. Supported forever. [Details](#)